



PROCOR CHEMICALS, INC.



Technical Data Sheet PRO BPX

DESCRIPTION	
<p>PRO BPX is an Cellulose Biopolymer LCM/Squeeze product which can be used as an "Aggressive LCM", "Squeeze Product" or "Pre-Cement Spacer" product. It is specially blended with loss circulation materials such as fibers, cellophane, resins and shells for ultimate performance and sealing capabilities. PRO BPX can be used in a wide range of applications, temperatures and densities. Tested and compatible with all water-based, oil-based and synthetic-based fluids.</p>	

PHYSICAL PROPERTIES	
Appearance	Blended granular and flaked material
Typical Particle Diameter (in microns)	10,200 micron
Odor	mild
Specific gravity	1.9
Manufacturing	Compliant with ISO QA (Quality Assurance) testing standards.
Solubility in water or brine	Non-Soluble (water/mud/brine dispersable)
Flash point	Not Applicable, dry product
Bulk Density	Uncompacted = 18 lb/ft ³ Compacted = 32 lb/ft ³ Average= 25 lb/ft ³
LC 50	139,081 ppm

STATIC SHEEN TEST RESULT				
Sample	Free oil	Oil Sheen	Oil Slick	Suitable to discharge
PRO BPX	No	No	No	Yes

APPLICATIONS
See page control, Moderate loss circulation, Severe loss circulation or High Fluid loss squeeze application.

ADVANTAGES
A single sack loss circulation material that can be used for any application, especially for large voids and vugular cavities, fractures and unconsolidated formations.

PACKAGING
PRO BPX is packaged in 25 lb. sx./ 80 sxs. per pallet.