



# PROCOR CHEMICALS, INC.



## Technical Data Sheet PRO V+™

### DESCRIPTION

**PRO V+™** is an Acid Soluble "Hybrid" LCM/Squeeze product which can be used as an "Aggressive LCM", "Squeeze Product" or "Pre-Cement Spacer" product. It is specially blended with loss circulation materials such as mineral fibers, cellophane acetate, pozzolonic agents and chiton for ultimate plugging and sealing capabilities. **PRO V+** can be used in a wide range of applications, temperatures and densities.

### PHYSICAL PROPERTIES

<b>Appearance</b>	Blended granular and flaked material
<b>Typical Particle Diameter (in microns)</b>	20- 2000 microns, avg coarse particles 750 - 1500 microns
<b>Odor</b>	mild
<b>Specific gravity</b>	1.9
<b>Manufacturing</b>	Compliant with ISO QA (Quality Assurance) testing standards.
<b>Solubility in water or brine</b>	Non-Soluble (water/mud/brine dispersable)
<b>Flash point</b>	Not Applicable, dry product
<b>Bulk Density</b>	Uncompacted = 18 lb/ft <sup>3</sup> Compacted = 32 lb/ft <sup>3</sup> Average= 25 lb/ft <sup>3</sup>
<b>LC 50</b>	139,081 ppm

### STATIC SHEEN TEST RESULT

Sample	Free oil	Oil Sheen	Oil Slick	Suitable to discharge
<b>PRO V+™</b>	No	No	No	Yes

### APPLICATIONS

See page control, Moderate loss circulation, Severe loss circulation or High Fluid loss squeeze application.

### ADVANTAGES

A single sack loss circulation material that can be used for any application, especially for large voids and vugular cavities, fractures and unconsolidated formations.

### PACKAGING

**PRO V+™** is packaged in 25 lb. sx./ 80 sxs. per pallet.